



# MIDI DRUM RACK

Drum rack with improved braking system for easy, safe and effective roll out of microfiber.

## Safe roll out of fiber

A drum safely attached to a drum rack with cones and ball bearings creates better fiber blowing results as it protects the fiber.

## Equipped with brakes

The midi drum rack is equipped with effective brakes, to avoid fiber overflow that could disrupt the fiber blowing job.

## Flexible lock function

During transport activate the lock function on the rack handle to secure the drum and the fiber.

## Easy management and transportation

The drum rack has small wheels making it easy to transport. Furthermore, you can easily fold it, minimizing its size, so it is possible to transport in small cars.

## COMPATIBLE WITH

NanoFlow MAX (Item No.: 101-190911001)  
• For fibers 0.8-4.5 mm

MicroFlow TOUCH (Item No.: 101-10051)  
• For microfibers 0.8-6.5 mm

MicroFlow LOG (Item No.: 101-171001001)  
• For microfibers 0.8-6.5 mm

MiniFlow RAPID (Item No.: 101-10031)  
• For cables 3-12 mm

## SPECIFICATIONS

Item No.:	103-211026001
Max. drum diameter:	800 mm
Drum center diameter:	20-93 mm
Max. drum width:	630 mm
Max. drum weight*:	70 kg
Weight:	8 kg
Length:	800 mm
Width:	535 mm
Height:	985 mm

\*With cable drums above 50 kg, always use the support arm delivered together with the drum rack.

