

OCPM-18

Optical CWDM Power Meter

Optical CWDM Power Meter is designed to measure both wavelength and optical power of multi wavelength optical signals in CWDM, FTTx, LTE, WCDMA, WDM-PON system, 3G that uses multiple optical carriers with different wavelengths. It is so compact and mechanically stable that it is suitable for outdoor field application.

Special Features

- Simultaneous measurement of both optical power and wavelength in CWDM system
- Compact size, excellent portability and easy operation
- Applicable for wavelength optical network such as CWDM, LTE, WiBro, 3G/4G, FTTx
- Also Works as a typical optical power meter
- Typical 5-pin Charger and USB data cable
- Color LCD and add to graphic display
- Light weight for on-site measurement
- Quick start operation, requiring no warm-up time and reducing testing time
- A robust, shock-proof, splash-proof design for field operation
- Save stored measured data to PC
- CE approval



Specifications

Parameter	Typical
Wavelength Range	1270 ~ 1610 nm
Number of Channels	18
Measuring Wavelength (nm)	1270/1290/1310/1330/1350/1370/1390/1410/1430 1450/1470/1490/1510/1530/1550/1570/1590/1610
Wavelength resolution	20nm
Dynamic range	+ 10dBm to -40dBm
Absolute accuracy	< ±0.5 dB
Power resolution	0.01 dB
Units	dBm / dB
Power supply	Rechargeable Lithium-Polymer Battery
Optical interface	SC/PC (standard), FC, LC, ST available
Guaranteed time of Operating	600 min (when fully charged)
Operating Temperature	0 ~ +50 °C
Dimension	78 x 155 x 35 mm
Weight	250g

Standard Package

P/N: **OCPM-18**

- 1 Power Meter Body (included Battery)
- 1 Body Rubber Case
- 1 USB Data Cable
- 1 Typical 5-pin Charger
- 1 Software CD
- 1 User Manual

12 / 01 / 01 12 : 00	
CWDM	
1270 nm	-27.40 dBm
1290 nm	-32.05 dBm
1310 nm	-33.54 dBm
1330 nm	-23.61 dBm
1350 nm	-20.33 dBm
1370 nm	-06.02 dBm
1390 nm	-35.46 dBm
1410 nm	-37.94 dBm
1430 nm	-34.81 dBm

12 / 01 / 01 12 : 00	
CWDM	
1450 nm	-33.86 dBm
1470 nm	-38.05 dBm
1490 nm	-35.16 dBm
1510 nm	-31.18 dBm
1530 nm	-30.33 dBm
1550 nm	-35.02 dBm
1570 nm	-27.57 dBm
1590 nm	-31.45 dBm
1610 nm	-12.26 dBm

TheFibers
CREATIVE FIBERS

TheFibers Inc.

#1103 K-Center Bldg, 1591-9 Kwanyang-Dong, Anyang-City, Korea

Tel: +82-31-381-6108 Fax: +82-31-381-6109 sales@thefibers.com